



Fade Hub Dimensions								
Product Description/ Dimensions in mm	Hub Width	PCD left	PCD right	Flange Distance left	Flange Distance Right	Spoke hole	Offset Spoke Hole left	Offset Spoke hole right
	A	B	C	D	E			
FADE MTB J-Bend								
NEWMEN FADE Hub MTB Front 15x110 J-Bend CL 28h & 32h	110	56,6	56,6	26,3	36,0	2,4	/	/
NEWMEN FADE Hub MTB Front 15-20x110 BOOST J-Bend 6Bolt 28h & 32h	110	54,8	37,8	27,5	39,0	2,4	/	/
NEWMEN FADE Hub MTB Rear 12x148 J-Bend 6Bolt & CL 28h & 32h	148	54,8	54,8	36,8	23,3	2,4	/	/
NEWMEN FADE Hub MTB Rear 12x157 J-Bend 6Bolt 28h & 32h	157	54,8	54,8	41,3	27,8	2,4	/	/
FADE MTB UL MTB J-Bend 6Bolt 28h & 32h								
NEWMEN FADE UL MTB Front 15x110 J-Bend 6Bolt 28h & 32h	110	53,9	37,8	27,1	39,4	2,4	/	/
NEWMEN FADE UL MTB Rear 12x148 J-Bend 6Bolt 28h & 32h	148	53,8	48,6	36,7	23,7	2,4	/	/

FADE MTB Straightpull 6Bolt & Centerlock								
Product Description/ Dimensions in mm	Hub Width	PCD left	PCD right	Flange Distance left	Flange Distance Right	Spoke hole	Offset Spoke Hole left	Offset Spoke hole right
	A	B	C	D	E			
NEWMEN FADE Hub MTB Front 15x110 Straight Pull 6Bolt & CL 28h	110	38,5	38,5	29,0	34,0	2,5	2,2	1,7
NEWMEN FADE Hub MTB Rear 12x148 Straight Pull 6Bolt & CL 28h	148	39,2	55,3	36,9	23,1	2,5	2	2,5
NEWMEN FADE Hub MTB Rear 12x157 Straight Pull 6Bolt & CL 28h	157	39,2	55,3	41,4	27,6	2,5	2	2,5

FADE Road Straightpull Centerlock								
NEWMEN Hub Road Front 12x100 Straight Pull CL 24h	100	40,4	40,4	24,0	29,1	2,5	1,7	1,7
NEWMEN Hub Road Rear 12x142 Straight Pull CL 24h	142	40,7	50,0	36,4	19,4	2,5	1,4	1,6
NEWMEN Hub Road Front 12x100 Straight Pull CL 28h	100	40,4	40,4	24,0	29,1	2,5	1,7	1,7
NEWMEN Hub Road Rear 12x142 Straight Pull CL 28h	142	40,7	50,0	36,4	19,4	2,5	1,4	1,6