



Fade Hub Dimensions								
Product Description/ Dimensions in mm	Hub Width	PCD left	PCD right	Flange Distance left	Flange Distance Right	Spoke hole	Offset Spoke Hole left	Offset Spoke hole right
	A	B	C	D	E			
FADE MTB J-Bend								
NEWMEN FADE Hub MTB Front 15x110 J-Bend CL 28h & 32h	110	56,6	56,6	26,3	36,0	2,4	/	/
NEWMEN FADE Hub MTB Front 15-20x110 BOOST J-Bend 6Bolt 28h & 32h	110	54,8	37,8	27,5	39,0	2,4	/	/
NEWMEN FADE Hub MTB Rear 12x148 J-Bend 6Bolt & CL 28h & 32h	148	54,8	54,8	36,8	23,3	2,4	/	/
NEWMEN FADE Hub MTB Rear 12x157 J-Bend 6Bolt 28h & 32h	157	54,8	54,8	41,3	27,8	2,4	/	/
Hub Basic FADE MTB 15x110 J-Bend CL 32h	110	44	44	27,7	35,7	2,7	/	/
Hub Basic FADE MTB 12x148 J-Bend CL 32h	148	57	57	35,9	22,2	2,7	/	/

Fade Hub Dimensions								
Product Description/ Dimensions in mm	Hub Width	PCD left	PCD right	Flange Distance left	Flange Distance Right	Spoke hole	Offset Spoke Hole left	Offset Spoke hole right
	A	B	C	D	E			

FADE MTB Straightpull 6Bolt & Centerlock								
NEWMEN FADE Hub MTB Front 15x110 Straight Pull 6Bolt & CL 28h	110	38,5	38,5	29,0	34,0	2,5	2,2	1,7
NEWMEN FADE Hub MTB Rear 12x148 Straight Pull 6Bolt & CL 28h	148	39,2	55,3	36,9	23,1	2,5	2	2,5
NEWMEN FADE Hub MTB Rear 12x157 Straight Pull 6Bolt & CL 28h	157	39,2	55,3	41,4	27,6	2,5	2	2,5
NEWMEN FADE Hub MTB Front 15x110 Straight Pull 6Bolt 32h	110	50,5	50,5	28,5	37,1	2,5	2,1	1,2
NEWMEN FADE Hub MTB Rear 12x148 Straight Pull 6Bolt & CL 32h	148	50,5	56,4	36,9	23,1	2,5	2	1,6
NEWMEN FADE Hub MTB Rear 12x157 Straight Pull 6Bolt & CL 32h	157	50,5	56,4	37,7	27,6	2,5	1,5	1,8

FADE Road Straightpull Centerlock								
NEWMEN Hub Road Front 12x100 Straight Pull CL 24h	100	40,4	40,4	24,0	29,1	2,5	1,7	1,7
NEWMEN Hub Road Rear 12x142 Straight Pull CL 24h	142	40,7	50,0	36,4	19,4	2,5	1,4	1,6
NEWMEN Hub Road Front 12x100 Straight Pull CL 28h	100	40,4	40,4	24,0	29,1	2,5	1,7	1,7
NEWMEN Hub Road Rear 12x142 Straight Pull CL 28h	142	40,7	50,0	36,4	19,4	2,5	1,4	1,6

FADE R Road Straightpull Centerlock								
NEWMEN Hub FADE R Front 12x100 Straight Pull CL 24h	100	40,5	40,0	22,7	29,5	2,5	2,5	1,0
NEWMEN Hub FADE R Rear 12x142 Straight Pull CL 24h	142	40,0	55,3	35,2	18,1	2,5	2,3	2
NEWMEN Hub FADE R Front 12x100 Straight Pull CL 28h	100	38,5	38,9	22,5	29,6	2,5	2,5	1,4
NEWMEN Hub FADE R Rear 12x142 Straight Pull CL 28h	142	40,1	55,0	35,2	18,2	2,5	1,3	2,2

FADE Road Classic J-Bend Centerlock								
NEWMEN Hub Classic Road Front 12x100 J-Bend CL 24h	100	44	44	21,49	31,84	2,7	/	/
NEWMEN Hub Classic Road Rear 12x142 J-Bend CL 24h	142	51,5	55,5	34,24	18,44	2,7	/	/
NEWMEN Hub Classic Gravel Front 12x100 J-Bend CL 28h	100	44	44	21,49	31,84	2,7	/	/
NEWMEN Hub Classic Gravel Rear 12x142 J-Bend CL 28h	142	51,5	55,5	34,24	18,44	2,7	/	/

Fade Hub Dimensions								
Product Description/ Dimensions in mm	Hub Width	PCD left	PCD right	Flange Distance left	Flange Distance Right	Spoke hole	Offset Spoke Hole left	Offset Spoke hole right
	A	B	C	D	E			

BASIC R Road J-Bend Centerlock								
NEWMEN hub BASIC R 12x100 J-Bend CL 24h	100	44	44	21,5	31,8	2,6	/	/
NEWMEN hub BASIC R 12x142 J-Bend CL 24h	142	56,5	56,5	34,2	18,4	2,6	/	/
NEWMEN hub BASIC R 12x100 J-Bend CL 28h	100	44	44	21,5	31,8	2,6	/	/
NEWMEN hub BASIC R 12x142 J-Bend CL 28h	142	56,5	56,5	34,2	18,4	2,6	/	/

Fade K Kids J-Bend hubs 6Bolt								
NEWMEN Hub FADE K 12x100 J-Bend 6B 24h	100	44	40	21,3	26,8	2,7	/	/
NEWMEN Hub FADE K 15x100 J-Bend 6B 24h	100	44	40	21,3	26,8	2,7	/	/
NEWMEN Hub FADE K 12x110 J-bend 6B 24h	110	44	40	26,7	26,8	2,7	/	/
NEWMEN Hub FADE K 15x110 J-bend 6B 24h	110	44	40	26,7	26,8	2,7	/	/