



Rim-/tire-width and pressure specifications

max pressure bar/psi		rim inner width								
WITH HOOK		18mm	19mm	20mm	21mm	22mm	23mm	24mm	25mm	30mm
tire width		Strem R.50 Strem R.66 Strem R.80	Strem R.38	Performance R.32	Advanced R.42	Strem C.35/C.38 Strem S.60/S.66 Strem TT.80	Advanced A.50	Strem A.49 Strem A.54	Performance 25	Beskar 30 Forge 30 Performance 30
23mm	0.90"	8,5	8,5	8,5	8,5	8,3	8,1			
25mm	1.00"	8,0	8,0	8,0	8,0	7,8	7,6	7,4		
28mm	1.10"	7,5	7,5	7,5	7,5	7,3	7,1	6,9	6,7	
30mm	1.20"	7,0	7,0	7,0	7,0	6,8	6,6	6,4	6,2	
32mm	1.25"	6,5	6,5	6,5	6,5	6,3	6,1	5,9	5,7	
33m	1.30"	6,1	6,1	6,1	6,1	5,9	5,7	5,5	5,3	
35mm	1.40"	5,6	5,6	5,6	5,6	5,4	5,2	5,0	4,8	
38mm	1.50"	5,3	5,3	5,3	5,3	5,1	4,9	4,7	4,5	
40mm	1.60"	5,0	5,0	5,0	5,0	4,8	4,6	4,4	4,2	4,0
45mm	1.80"	4,8	4,8	4,8	4,8	4,6	4,4	4,2	4,0	3,8
50mm	2.0"	4,6	4,6	4,6	4,6	4,4	4,2	4,0	3,8	3,6
53mm	2.1"		4,5	4,5	4,5	4,3	4,1	3,9	3,7	3,5
55mm	2.2"			4,4	4,4	4,2	4,0	3,8	3,6	3,4
58mm	2.3"				4,3	4,1	3,9	3,7	3,5	3,3
61mm	2.4"					4,0	3,8	3,6	3,4	3,2
63mm	2.5"						3,7	3,5	3,3	3,1
66mm	2.6"							3,4	3,2	3,0
68mm	2.7"								3,1	2,9
71mm	2.8"									2,8
76mm	3.0"									

max pressure bar/psi		rim inner width	
HOOKLESS		24mm/25mm	30mm
tire width		Advanced G.34 Evolution X.R.25 Advanced X.R.25/36	Phase 30 Evolution A.30 Evolution E.G.30
23mm	0.90"		
25mm	1.00"		
28mm	1.10"		
30mm	1.20"		
32mm	1.25"	4,0	
33m	1.30"	4,0	
35mm	1.40"	4,0	
38mm	1.50"	4,0	
40mm	1.60"	4,0	
45mm	1.80"	3,5	
50mm	2.0"	3,5	3,0
53mm	2.1"	3,3	3,0
55mm	2.2"	3,1	3,0
58mm	2.3"	2,9	2,9
61mm	2.4"	2,7	2,7
63mm	2.5"	2,6	2,6
66mm	2.6"		2,5
68mm	2.7"		2,4
71mm	2.8"		2,3
76mm	3.0"		

ideal tire/rim width combination

possible combination

DO NOT EXCEED THE MAX. PRESSURE STATED ON THE RIM / TIRE